Meet Zoe

Slim downlight



Slim and adaptable, Zoe is perfectly suited to everyday needs

- Uniform light surface
- Product height of only 12 mm: fits various ceiling types
- Choice of 3000 K or 4000 K to suit application use
- Replaces conventional downlights with 1x18 W, 1x26 W and 2x18 W CFL and offers up to 50 % energy saving
- Tool-free installation



Available in 600, 900 and 1500 lumen versions



3000K & 4000K colour temp

Ideal for...



Corridors



Reception areas



Offices and meeting rooms




Schools and universities

Zoe 900 lm

83Llm/W -<u>A</u>-

cd/klm ULOR: 0% DLOR: 100% LOR: 100%



Installation/Mounting

• Recessed installation into a wide range of ceiling types

Material/Finish

Body: Aluminum white finish

Diffuser: Polycarbonate

Light source information

- 600 lm (8 W), 900 lm (12 W) and 1500 lm (18 W), up to 85 lm/W
- Color temperatures: 4000 K and 3000 K
- 25 000 hour rated life (@L70B50, Ta 25°C)
- McAdam (initial): 5 step

Specification

- Class II electrical
- IP44
- IK02

Ordering guide

Description	Wt (Kg)	SAP Code	Cat. No.
ZOE LED DL 110 600 840	0.25	96666088	ZO600Z4K
ZOE LED DL 160 900 840	0.4	96666089	ZO900Z4K
ZOE LED DL 210 1500 840	0.55	96666090	ZO1500Z4K
ZOE LED DL 110 600 830	0.25	96666092	ZO600Z3K
ZOE LED DL 160 900 830	0.4	96666093	ZO900Z3K
ZOE LED DL 210 1500 830	0.55	96666094	ZO1500Z3K

830-3000K, 840-4000K

